

SIZE	LOAD INDEX	LOAD MOUNTING	AIR PRESSURE																			
			40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115	120	125		
185R14C	102/100	tandem (Kg)	635	670	700	730	780	800														
		single (Kg)	675	710	740	775	825	850														
215/70R14C	106/104	tandem (Kg)		765	835	900																
		single (Kg)		810	880	950																
205/70R15C	106/104	tandem (Kg)		670	730	785	845	900														
		single (Kg)		705	770	830	890	950														
225/70R15C	112/110	tandem (Kg)		790	860	975	995	1060														
		single (Kg)		835	905	##	1050	1120														
195/75R16C	107/105	tandem (Kg)	660	725	785	850	870	890	925													
		single (Kg)	700	765	835	900	920	950	975													
205/75R16C	113/111	tandem (Kg)	660	700	765	825	885	940	1000	1090												
		single (Kg)	700	745	810	875	935	1000	1060	1150												
225/75R16C	118/116	tandem (Kg)				990	1060	1130	1180	1250												
		single (Kg)				##	1100	1170	1250	1320												
7.00R16	113/112	tandem (Kg)	750	800	870	915	950	1005	1085	1120												
		single (Kg)	800	850	925	965	1000	1060	1020	1150												
7.50R16	122/120	tandem (Kg)	700	770	840	905	970	1035	1095	1160	1220	1280	1340	1400								
		single (Kg)	750	825	900	970	1040	1105	1175	1240	1305	1370	1435	1500								
205/75R17.5	124/122	tandem (Kg)						990	1050	1110	1170	1230	1285	1345	1400	1440	1500					
		single (Kg)						1030	1090	1150	1210	1275	1330	1390	1450	1540	1600					
215/75R17.5	126/124	tandem (Kg)						1135	1200	1270	1340	1405	1470	1535	1600							
		single (Kg)						1205	1275	1350	1420	1490	1560	1630	1700							
9.00R20	141/137	tandem (Kg)								1760	1850	1940	2030	2120	2210	2300						
		single (Kg)								1970	2070	2175	2275	2375	2475	2575						
10.00R20	146/143	tandem (Kg)								1935	2040	2140	2240	2340	2440	2535	2630	2725				
		single (Kg)								2130	2245	2355	2465	2575	2685	2790	2895	3000				
11.00R20	150/147	tandem (Kg)								1925	2030	2130	2230	2330	2425	2520	2620	2715	2805	2900		
		single (Kg)								2095	2205	2315	2420	2530	2635	2740	2845	2945	3050	3150		
12.00R20	154/149	tandem (Kg)								2045	2150	2260	2365	2470	2570	2675	2775	2875	2975	3075		
		single (Kg)								2225	2345	2460	2575	2690	2800	2915	3025	3135	3240	3350		
11.00R22	152/149	tandem (Kg)								2060	2170	2275	2385	2490	2595	2695	2800	2900				
		single (Kg)								2310	2460	2550	2670	2790	2905	3020	3135	3250				
10R22.5	141/137	tandem (Kg)								2060	2170	2275	2385	2490	2595	2695	2800	2900				
		single (Kg)								2300	2420	2540	2660	2780	2895	3010	3125	3240				
11R22.5	150/147	tandem (Kg)								2160	2275	2390	2500	2610	2720	2830	2935	3040	3145	3250		
		single (Kg)								2490	2625	2755	2885	3010	3135	3260	3385	3510	3630	3750		
12R22.5	150/146	tandem (Kg)								2110	2225	2335	2445	2550	2660	2765	2870	2970	3075			
		single (Kg)								2370	2495	2620	2740	2860	2980	3100	3220	3335	3450			
275/80R22.5	151/148	tandem (Kg)								2400	2500	2600	2650	2770	2890	3000	3080	3160	3250			
		single (Kg)								2500	2630	2740	2900	3020	3140	3250	3350	3450	3550			
305/75R24.5	154/149	tandem (Kg)								1635	1720	1805	1890	1975	2055	2140	2220	2300				
		single (Kg)								1775	1870	1965	2055	2145	2235	2325	2415	2500				
385/65R22.5	160	tandem (Kg)								1935	2040	2140	2240	2340	2440	2535	2630	2725				
		single (Kg)								2130	2245	2355	2465	2575	2685	2790	2895	3000				
295/80R22.5	154/150	tandem (Kg)								1930	2030	2130	2230	2330	2425	2520	2620	2715	2805	2900		
		single (Kg)								2095	2205	2315	2420	2530	2635	2740	2845	2945	3050	3150		
305/80R22.5	152/148	tandem (Kg)								2045	2150	2260	2365	2470	2570	2675	2775	2875	2975	3075		
		single (Kg)								2225	2345	2460	2575	2690	2800	2915	3025	3135	3240	3350		
305/75R24.5	158	tandem (Kg)								2060	2170	2275	2385	2490	2595	2695	2800	2900				
		single (Kg)								2310	2430	2550	2670	2790	2905	3020	3135	3250				
305/75R24.5	160	tandem (Kg)								2130	2245	2355	2465	2575	2685	2790	2895	3000				
		single (Kg)								2380	2505	2630	2755	2875	2995	3115	3235	3350				
305/75R24.5	154/150	tandem (Kg)								1990	2095	2200	2305	2405	2505	2605	2705	2805	2900			
		single (Kg)								2165	2275	2390	2500	2615	2720	2830	2940	3045	3150			
305/75R24.5	154/149	tandem (Kg)								1995	2100	2205	2305	2410	2510	2610	2710	2805	2905	3000		
		single (Kg)								2160	2275	2385	2500	2610	2720	2825	2935	3040	3145	3250		
305/75R24.5	154/149	tandem (Kg)								2095	2205	2315	2420	2530	2635	2740	2845	2945	3050	3450		
		single (Kg)								2295	2415	2535	2655	2770	2885	3000	3115	3225	3340	3450		
305/75R24.5	154/149	tandem (Kg)								2185	2300	2415	2525	2640	2750	2860	2970	3075				
		single (Kg)								2380	2505	2630	2755	2875	2995	3115	3235	3350				
305/75R24.5	154/149	tandem (Kg)								2095	2205	2315	2420	2530	2635	2740	2845	2945	3050	3150		
		single (Kg)								2360	2485	2610	2730	2850	2970	3090	3205	3320	3435	3550		
305/75R24.5	154/150	tandem (Kg)								2225	2345	2460	2575	2690	2800	2915	3025	3135	3240	3350		
		single (Kg)								2490	2625	2755	2885	3010	3135	3260	3385	3510	3630	3750		
305/75R24.5	154/149	tandem (Kg)								1925	2045	2160	2275	2385	2500	2610	2720	2825	2935	3040	3145	3250
		single (Kg)								2220	2360	2490	2625	2755	2885	3010	3135	3260	3385	3510	3630	3750
305/75R24.5	158	tandem (Kg)								2920	3075	3225	3375	3525	3675	3820	3965	4110	4250			
		single (Kg)								3090	3255	3415	3575	3735	3890	4045	4195	4350	4500			